

# **LOW PRESSURE AIR CONTROL SYSTEMS**

In-Line Air Filters and Air Filter/Regulator Systems



# Air filters and regulators for low-pressure applications

FEATURES	BENEFIIS
• Remove contaminants down to 5 microns	• Dry air for all air-operated equipment
Perfect point-of-use filters for air-operated     equipment	Clean and dry air increases equipment life     and product performance
Specifically designed for low pressure     applications	<ul> <li>Easy to install in your existing compressed air system</li> </ul>
Systems with up to two air controls for multiple drops	Reduce total number of filters required     and lower costs
Reusable edge-type filter element design	Lower total cost of ownership
• Auto-drain valves on in-line filter and coalescer	Eliminate manual emptying of filters



PROVEN QUALITY. LEADING TECHNOLOGY.

## **Technical Specifications & Ordering Information**

### **Air Control Systems**

		Max. Air		
Part Number	Description	Inlet Pressure	Weight	Max. CFM
234398	Air control unit, filtered main air outlet, two regulated outlets	160 psi (1.1 MPa, 11 bar)	5 lb 12 oz (2.6 kg)	120 CFM – Filter 50 CFM – Air Regulator
234399	Air control unit, filtered main air outlet with gauge, two regulated outlets	160 psi (1.1 MPa, 11 bar)	6 lb 4 oz (2.8 kg)	120 CFM – Filter 50 CFM – Air Regulator
234400	Air control unit, filtered main air outlet with gauge, three regulated outlets	160 psi (1.1 MPa, 11 bar)	7 lb 13 oz ( 3.5 kg)	120 CFM – Filter 50 CFM – Air Regulator
234411	Air control unit, filtered main air outlet, two regulated outlets	160 psi (1.1 MPa, 11 bar)	4 lb 13 oz ( 2.2 kg)	75 CFM – Filter 50 CFM – Air Regulator

#### **Air Filters**

Part Number	Description	Inlet	Outlet	Max. Air Inlet Pressure	Weight	Max. CFM
234396	Air filter, bare	1/2" npt (f)	3/8" npt (f)	175 psi (1.2 MPa, 12 bar)	3 lb 10 oz (1.6 kg)	120 CFM
234410	Air filter, bare	1/2" npt (f)	3/8" npt (f) 1/4" npt (f) plugged	175 psi (1.2 MPa, 12 bar)	2 lb 11 oz (1.2 kg)	75 CFM
234412	Air filter, quick coupler	1/4" npt (f)	1/4" npt (f) 1/4" npt (f) plugged	175 psi (1.2 MPa, 12 bar)	3 lb 2 oz (1.4 kg)	75 CFM

#### **Instruction Manual**

309923

All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

Call today for product information or to request a demonstration. **1.877.84GRACO** (1-877-844-7226) or visit us at www.graco.com.