GL-1 Injector

Automatic Lubrication System



Graco's captured seal design is the best in the business!

- Test results show the difference–GL-1 injectors showed no seal leakage at 215,000 cycles
- Seals last 5 times longer than the competition's!
- Combine with GL-11s and GL-32s in the same Single Line Parallel System for a full range of outputs





System Setup Tips

- Run branches off main line and "Tee Out" to banks of injectors instead of in-series
- Locate injectors as close to bearings as possible to minimize line length to bearing to enable max pressure to reach injectors
- Place pressure switch beyond last injector
- Use large diameter tubing (1/4 in.) to lessen restrictions
- Make sure you have enough pressure to achieve normal 2,500 psi (172 bar)
- Make sure you vent down to the minimum reset pressure of your smallest injector

To adjust:

- 1. Loosen the lock nut
- 2. Rotate 5/8 inch output adjustment nut clockwise to decrease grease outputdecrease the travel of the piston
- 3. Rotate 5/8 inch output adjustment nut counter-clockwise to increase grease output-increase the travel piston




©2011 Graco Inc. 340447 Rev. A 05/2011 Printed in China. All other brand names or marks are used for identification purposes and ar trademarks of their respective owners. All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

Precision-honed Components for Reliable Operation in the Harshest Environments

Technical Specifications

Maximum operating pressure	3500 psi (241 bar)
Minimum operating pressure	1850 psi (128 bar)
Suggested operating pressure	2500 psi (172 bar)
Reset pressure	600 psi (4.1 bar)
Output volume per cycle	0.008-0.08 in ³ (0.13-1.13 c ³)
Recommended fluids	Uses NLGI #2 grease down to 32° F (0° C)
Instruction manual	308953
Design Guide	309
Zerk Fitting Outlet	1/8 in npt
Supply Line Outlet	1/4 in npt
Inlet	3/8 in npt



Contact us today!

Send an E-mail to info_APLube@graco.com for product information or visit us at www.graco.com

Australia office Tel: +61 3 9468 8500

115119

114916

China Office Tel: +86 21 649 50088

GL-1 Clear Plastisol Injector Cover

GL-1 & GL-11 Zerk Fitting and Cap Kit

India Office Tel: +91 124 435 4208 Japan office Tel: +81 45 593 7300

Korea office Tel: +82 31 476 9400