# **GLC 2200 Controller**



**Compact and Versatile for All Automatic Lubrication Systems** 



## **Intelligent Feedback**

The GLC family just got bigger. And now you can make smarter decisions about how you control your equipment. Choose the rugged GLC 2200 controller for in-cab monitoring of any 9-30 VDC system.

## Ordering Information

24N468 GLC 2200 Controller

24P314 Five foot (1.5 M) wiring harness with 10 pin connector and color

coded flying leads



# **Control for Your Investment**

You spend a lot on your equipment. The GLC 2200 controller helps protect components by alerting you to lube event failures and low lubrication levels. You have peace of mind knowing your investment is being protected.

## **External Mounting Tabs**

Easy to mount without having to open up the control box.

## **Monitoring LEDs**

LEDs let you know what your system is doing at a glance.

## Digital Readout

Easy to read digital display makes it simple to program and monitor your equipment.

#### Visual and Audible Alarms

In-cab visual and audible alarms let the operator know your equipment needs attention. Or set up a remote alarm to alert service or maintenance staff.

#### Intuitive Control

Simple icon based push buttons make programming easy.

#### Plug and Play

Color coded wiring harness with flying leads and easy to follow wiring diagrams makes installations efficient.

#### **Technical Specs**

Physical Dimensions	2.75 in. (70 mm) wide x 5.53 in. (140 mm) high x 1.38 in. (35 mm) deep
Protection Grade	IP54
Operating Temperature	-40° F to 176° F (-40° C to 80° C)
Power Source	DC 9-30 VDC
Approvals	CE, ISO 13766

## Contact us today!

