



Plating Applications

Graco Process Solutions



Process Applications for Plating

- Pumping of acids and bases
- Drum transfer
- Tank and pit evacuation
- Chemical/pH balance
- Filter press sludge removal

PROVEN QUALITY. LEADING TECHNOLOGY.

Husky™ Diaphragm Pumps

Pump, Transfer and Evacuate Acids and Bases

Husky 515, 1050, 1590 and 2150 polypropylene diaphragm pumps

- Extreme durability in corrosive environments

Popular Models

D52911	Husky polypropylene 515, 1/2 in (12.7 mm) npt connection size Maximum flow 15 gpm (56 l). Order D5B911 for bspt.
649034	Husky polypropylene 1050, 1 in (25.4 mm) flange connection Maximum flow 50 gpm (189 l)
DB2911	Husky polypropylene 1590, 1-1/2 in (38.1 mm) flange connection Maximum flow 90 gpm (340 l)
DF2911	Husky polypropylene 2150, 2 in (50.8 mm) flange connection Maximum flow 150 gpm (567 l)



Husky 515 Poly



Husky 1050 Poly



Husky 1590 Poly



Husky 2150 Poly

Chemical and pH Balance

Husky 205 polypropylene and PVDF diaphragm pumps

- Remote control option using external controller

Popular Models

D12091	Husky polypropylene 205, 1/4 in (6.3 mm) connection size Maximum flow 5 gpm (18 l)
D150A1	Husky PVDF 205, 1/4 in (6.3 mm) inch connection size Maximum flow 5 gpm (18 l)



D150A1 PVDF



D12091 Poly

Filter Press Sludge Removal

Husky 1050, 1590 and 2150 SST and aluminum diaphragm pumps

- Ideal for abrasive and corrosive applications

Popular Models

651158	Husky stainless steel 1050, 1 in (25.4 mm) npt connection size Maximum flow 50 gpm (189 l). Order 651176 for bspt.
DB4366	Husky stainless steel 1590, 1-1/2 in (38.1 mm) npt connection size Maximum flow 90 gpm (340 l). Order DBD366 for bspt.
DF4366	Husky stainless steel 2150, 2 in (50.8 mm) npt connection size Maximum flow 150 gpm (567 l). Order DFD366 for bspt.
647023	Husky aluminum 1050, 1 in (25.4 mm) npt connection size Maximum flow 50 gpm (189 l). Order 647104 for bspt.
DB3366	Husky aluminum 1590, 1-1/2 in (38.1 mm) npt connection size Maximum flow 90 gpm (340 l). Order DBC366 for bspt.
DF3366	Husky aluminum 2150, 2 in (50.8 mm) npt connection size Maximum flow 150 gpm (567 l). Order DFC366 for bspt.



Husky 1050 SST



Husky 1050 Aluminum

All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

Call today for product information or to request a demonstration.

877.84GRACO (1-877-844-7226) or visit us at www.graco.com.

©2011 Graco Inc. Electronic Copy Only Rev. A 1/11 Printed in the U.S.A.
All other brand names or marks are used for identification purposes and are trademarks of their respective owners.

