



固瑞克一体式隔膜泵

适用于工业与卫生级应用场合



固瑞克一体式隔膜泵助您提升生产效率

- 适用于广泛的泵送材料，耐磨性强，可靠性高
- 工作寿命4倍于普通膜片，降低替换成本，减少停机时间
- 一体式设计便于膜片清洗，节省清洗材料成本与时间

工业泵(内部自配 PTFE/EPDM 一体式膜片)

订货号	泵尺寸	中心体	浸液部件	阀座	球阀	接口类型
24N093	0.5 in	Poly	Poly	Poly	PTFE	NPT
24N094	0.5 in	Poly	Poly	Poly	PTFE	BSPT
24N095	0.5 in	Poly	PVDF	PVDF	PTFE	NPT
24N096	0.5 in	Poly	Acetal	Acetal	PTFE	NPT
24N097	0.5 in	Poly	Acetal	SST	SST	NPT
24N098	0.5 in	Poly	Acetal	Acetal	PTFE	BSPT
24N257	0.75 in	Poly	AL	Acetal	PTFE	NPT
24N258	0.75 in	Poly	AL	SST	PTFE	NPT
24N259	0.75 in	Poly	AL	SST	SST	NPT
24N260	0.75 in	Poly	SST	Acetal	PTFE	NPT
24N261	0.75 in	Poly	SST	SST	PTFE	NPT
24N262	0.75 in	Poly	SST	SST	SST	NPT
649020	1.0 in	Poly	Poly	SST	PTFE	NPT
649007	1.0 in	Poly	Poly	Poly	PTFE	NPT
651011	1.0 in	AL	SST	SST	PTFE	NPT
649385	1.0 in	Poly	PVDF	PVDF	PTFE	NPT
647022	1.0 in	AL	AL	SST	SST	NPT
647032	1.0 in	AL	AL	SST	PTFE	NPT
649007	1.0 in	Poly	Poly	Poly	PTFE	Center Flange
649035	1.0 in	Poly	Poly	Poly	PTFE	End Flange
649399	1.0 in	Poly	PVDF	PVDF	PTFE	End Flange
651005	1.0 in	AL	SST	SST	SST	NPT
651011	1.0 in	AL	SST	SST	PTFE	NPT
651034	1.0 in	AL	SST	SST	PTFE	BSPT
651163	1.0 in	Poly	SST	SST	PTFE	NPT
24B781	1.5 in	AL	SST	SST	PTFE	NPT
24B761	1.5 in	AL	Poly	SST	PTFE	NPT
24B760	1.5 in	AL	Poly	Poly	PTFE	NPT
24B832	1.5 in	AL	PVDF	PVDF	PTFE	NPT
24B780	1.5 in	SST	SST	SST	PTFE	NPT
24B759	1.5 in	SST	Poly	Poly	PTFE	NPT
24B758	1.5 in	SST	PVDF	PVDF	PTFE	NPT
24G411	1.5 in.	AL	AL	SST	PTFE	BSPT
24J358	1.5 in.	AL	AL	SST	PTFE	NPT
24J359	1.5 in.	AL	AL	SST	Acetal	NPT
24B801	2.0 in	AL	SST	SST	PTFE	NPT
24B782	2.0 in	AL	AL	SST	PTFE	NPT
24B765	2.0 in	AL	Poly	SST	PTFE	NPT
24B764	2.0 in	AL	Poly	Poly	PTFE	NPT
24B833	2.0 in	AL	PVDF	PVDF	PTFE	NPT
24B783	2.0 in	SST	SST	SST	PTFE	NPT
24B763	2.0 in	SST	Poly	Poly	PTFE	NPT
24B762	2.0 in	SST	PVDF	PVDF	PTFE	NPT
24J360	2.0 in	AL	AL	SST	Acetal	NPT
24G413	2.0 in	AL	AL	SST	PTFE	BSPT

*仅列出通用产品型号，更多产品信息请参考300435流体设备综合样本。

FDA卫生泵(内部自配 PTFE/EPDM 一体式膜片)

订货号	泵尺寸	流体进口/ 出口尺寸	中心体	浸液 部件	阀座	球阀	O形圈
FD5113	0.5 in	1.0 in	SST	SST	SST	PTFE	PTFE
FD5613	0.5 in	1.0 in	SST	SST	SST	PTFE	EPDM
FD1113	1.0 in	1.5 in	SST	SST	SST	PTFE	PTFE
FD1213	1.0 in	1.5 in	SST	SST	SST	PTFE	EPDM
FD2113	1.5 in	2.0 in	SST	SST	SST	PTFE	PTFE
FD2213	1.5 in	2.0 in	SST	SST	SST	PTFE	EPDM
FD3113	2.0 in	2.5 in	SST	SST	SST	PTFE	PTFE
FD3213	2.0 in	2.5 in	SST	SST	SST	PTFE	EPDM
FD3133	2.0 in	2.5 in	SST	SST	SST	NEO/ SST	PTFE

高级卫生泵(内部自配 PTFE/EPDM 一体式膜片)

订货号	泵尺寸	流体进口/ 出口尺寸	中心体	浸液 部件	阀座	球阀
1590 高级卫生泵						
SABA13*	1.5 in	2.0 in	SST	SST	SST	PTFE
SBBA13	1.5 in	2.0 in	SST	SST	SST	PTFE
3150 高级卫生泵						
SA13A1	2.0 in	1.5 in	SST	SST	SST	PTFE
SA23A1	2.0 in	2.0 in	SST	SST	SST	PTFE
SA33A1	2.0 in	3.0 in	SST	SST	SST	PTFE
SA3361	2.0 in	3.0 in	SST	SST	SST	Santoprene
SA53A1	2.0 in	3.0 in x 2.0 in	SST	SST	SST	PTFE
SA43A1	2.0 in	4.0 in	SST	SST	SST	PTFE

*包括检漏仪

高级卫生泵和工业泵升级套件*

订货号	产品描述
24N321	0.5 in泵升级套件
289224	1.0 in泵升级套件
289225	1.5 in泵升级套件
289226	2.0 in泵升级套件

*包括新的空气端膜片压板

技术参数

材料/构造:	工作寿命:
浸液端为FDA卫生级PTFE材料	相比固瑞克两片式PTFE膜片，
空气端为FDA卫生级EPDM材料	工作寿命高达4倍
温度范围:	安全:
4°C至82°C (40°F至180°F)	符合FDA21CFR 177.1550 (PTFE) 和FDA21CFR 177.2600 (EPDM)标准

本文档包含的所有文字及图像数据均以发布时的最新产品信息为依据。固瑞克公司保留随时更改的权利，恕不提前通知。

美国固瑞克（香港）有限公司上海代表处

上海市黄浦区中山南路1029号7号楼

200011

电话: 021-6495 0088 传真: 021-6495 0077

www.graco.com

©2012, 2009, 2007 Graco Inc. 338940C-CN 06/2012 Printed in China

All other brand names or marks are used for identification purposes and are trademarks of their respective owners.

