



Car Wash Applications

Graco Process Solutions



Common Materials

- Pre-soak detergents
- Tire cleaners
- White wall cleaners
- Engine cleaners
- Soaps
- Rinse chemicals

PROVEN QUALITY. LEADING TECHNOLOGY.

Husky™ Diaphragm Pumps

For Chemical Supply

Husky 205, 307 and 515 polypropylene diaphragm pumps

- Features polypropylene and PTFE elastomers
- Reliable, non-stall, air valve for years of dependable performance

Popular Models for Chemical Supply

- D12091 Husky 205, 1/4 inch (6.35 mm) connection size
Maximum flow 5 gpm (19 lpm)
- D32911 Husky 307, 3/8 inch (9.5 mm) connection size
Maximum flow 7 gpm (26.5 lpm)
- D52911 Husky 515, 1/2 inch (12.7 mm) connection size
Maximum flow 15 gpm (56.8 lpm)

Popular Models for Soap and Rinse Solutions

- D12091 Husky 205, 1/4 inch (6.35 mm) connection size
Maximum flow 5 gpm (19 lpm)
- D32955 Husky 307, 3/8 inch (9.5 mm) connection size
Maximum flow 7 gpm (26.5 lpm)
- D52955 Husky 515, 1/2 inch (12.7 mm) connection size
Maximum flow 15 gpm (56.8 lpm)



Husky 205



Husky 307



Husky 515

All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

Call today for product information or to request a demonstration.

877.84GRACO (1-877-844-7226) or visit us at www.graco.com.

©2011 Graco Inc. Electronic Copy Only Rev. A 1/11 Printed in the U.S.A.
All other brand names or marks are used for identification purposes and are trademarks of their respective owners.

