



Oil Drilling Applications

Graco Process Solutions



Common Materials

- Fluid Transfer
- Spill containment
- High pressure cleaning

PROVEN QUALITY. LEADING TECHNOLOGY.

Husky™ Diaphragm Pumps

for Fluid Transfer and Spill Containment

Husky 1050, 1590, 2150 and 3275 aluminum diaphragm pumps

- Features TPE seats, acetyl balls and TPE diaphragms
- Three-way pilot valve for true non-sticking operation
- Fewer moving parts for increased durability and less repair time
- Externally serviceable for quick, inexpensive repairs

Popular Models

647666	Husky 1050, 1 inch (2.5 cm) connection size
DB3525	Husky 1590, 1-1/2 inch (3.8 cm) connection size
DF3525	Husky 2150, 2 inch (5 cm) connection size
DK3525	Husky 3275, 3 inch (7.6 cm) connection size



Husky 1050



Husky 1590



Husky 2150



Husky 3275

Hydra-Clean™ Pressure Washers

for High Pressure Cleaning

Hydra-Clean Pressure Washers

- Available in ratios of 12:1, 23:1, 30:1 and 45:1
- Choose cart or wall mount units
- Reduced water consumption
- Handles materials up to 200°F
- Supports multiple guns
- Pressure range of 1250 to 4500 psi (86 to 310 bar)

Popular Models

247553	Hydra-Clean 30:1 Cart Mount
247554	Hydra-Clean 30:1 Wall Mount
258664	Hydra-Clean 45:1 Cart Mount
258665	Hydra-Clean 45:1 Wall Mount



Hydra-Clean

All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

Call today for product information or to request a demonstration.
877.84GRACO (1-877-844-7226) or visit us at www.graco.com.

©2011 Graco Inc. Electronic Copy Only Rev. A 1/11 Printed in the U.S.A.
All other brand names or marks are used for identification purposes and are trademarks of their respective owners.

